

**TRELLEBORG COATED SYSTEMS US, INC.**  
**EXCELLENCE THROUGH INNOVATION**

**FD0005MVM015**  
**.015" Red Fluorosilicone**

COATED FABRIC PROPERTIES	Test Method	REQUIREMENTS
Color	Visual	Red
Fairprene Scrubs	Trelleborg Test Method	Minimum of 500.00 strokes
Gauge	ASTM D 751-89, sec. 9	Range of 0.014 to 0.017 inches
Grab Tensile - Fill	ASTM D 751-89, sec. 11	Minimum of 100.00 lbf
Grab Tensile - Warp	ASTM D 751-89, sec. 11	Minimum of 100.00 lbf
Mullen Burst	ASTM D 751-89, sec. 18.3	Minimum of 150.00 psi
Mullen Hydrostatic	ASTM D 751-89, sec. 34.2	Minimum of 100.00 psi
State of Cure	Trelleborg Test Method	Pass
Volume Change	ASTM D 471	Record Only, %
Width	ASTM D 751-89, sec. 8	43" Untrimmed

---

Original Date: 5/7/2015

The information supplied herein is based upon information currently available on the subject. It is offered as a possible helpful guide. Trelleborg Coated Systems US, Inc., makes no guarantee of results and assumes no obligation or liability whatsoever in connection with this information. THERE ARE NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING THE WARRANTY FOR FITNESS OF USE OR OF MERCHANTABILITY, UNLESS EXPRESSLY SET FORTH HEREIN.

TRELLEBORG COATED SYSTEMS US, INC.

715 Railroad Avenue

Rutherfordton, NC 28139

1-800-635-9350 - fax (828) 394-5005

